

Inspection Robot Using Accelerometer

Prof. S. R. Shekokar¹, Mr. Tejas Ugale², Mr Hemant Warake³, Mr. Mehul Chaudhari⁴, Mr.Kunal Lule⁵, Mr. Nikhil Mandawale⁶, Mr. Jayesh Mahajan⁷, Mr. C. D. Patil⁸

Professor, Department of Mechanical Engg, Dr. V. B. Kolte College of Engineering, Malkapur, India ¹

Students, Department of Mechanical Engg, Dr. V. B. Kolte College of Engineering, Malkapur, India ^{2,3,4,5,6,7,8}

ABSTRACT

The rapid growth of industrial automation has increased the need for efficient, safe, and intelligent inspection systems. This project presents the design and development of an inspection robot powered by solar energy and controlled using an accelerometer-based system. The robot is specifically intended for applications in hazardous or hard-to-reach environments such as pipelines, railway tracks, industrial plants, and disaster-prone areas, where human intervention may be risky or inefficient. The proposed system integrates a solar panel as the primary power source, enabling sustainable and eco-friendly operation. The solar energy is stored in rechargeable batteries, ensuring continuous functionality even during low sunlight conditions. An accelerometer sensor is employed as a motion control interface, allowing the user to control the robot's direction through hand gestures or tilt movements. This enhances ease of operation and provides a more intuitive control mechanism compared to conventional joystick or button-based systems. The robot is equipped with a microcontroller unit that processes signals from the accelerometer and translates them into movement commands for the motors. Additionally, the system can be integrated with a wireless communication module (such as RF or Bluetooth) to enable remote operation. A camera module or sensors may also be added for real-time monitoring, obstacle detection, and inspection purposes, thereby increasing the robot's effectiveness in surveillance and data collection tasks. The use of solar energy significantly reduces dependency on external power sources and minimizes operational costs, making the system energy-efficient and environmentally friendly. Furthermore, the accelerometer-based control provides improved flexibility and precision in navigation, making the robot suitable for complex terrains and confined spaces. In conclusion, the solar-powered inspection robot using an accelerometer offers a reliable, cost-effective, and innovative solution for modern inspection needs. It enhances safety, reduces human effort, and promotes the use of renewable energy in robotic systems.

Keywords: *Inspection Robot, Solar Power, Accelerometer, Renewable Energy, Wireless Control, Automation, Remote Monitoring etc.*

1. INTRODUCTION

In recent years, the demand for automation in inspection and monitoring tasks has increased significantly due to rapid industrialization and technological advancement. Industries such as manufacturing, oil and gas, railways, and power plants require continuous inspection of equipment, pipelines, and infrastructure to ensure safety, efficiency, and reliability. Traditional inspection methods often involve human intervention, which can be time-consuming, costly, and sometimes hazardous, especially in environments that are difficult to access or unsafe for humans. To overcome these challenges, robotic inspection systems have emerged as an effective and innovative solution. The Inspection Robot Using Accelerometer and Solar Power is a modern approach that combines robotics, renewable energy, and sensor-based control systems. This project focuses on developing a mobile robot that can be remotely operated using an accelerometer sensor while being powered by solar energy. The integration of these technologies not only enhances the functionality of the robot but also makes it energy-efficient and environmentally sustainable. One of the key features of

this system is the use of solar power as the primary energy source. With the increasing concern over the depletion of fossil fuels and environmental pollution, renewable energy sources such as solar energy have gained significant importance. By incorporating solar panels into the robot, the system can harness sunlight to generate electrical energy, which is stored in rechargeable batteries. This ensures continuous operation with minimal dependency on external power supplies, making the robot suitable for long-duration inspection tasks in remote locations. Another important aspect of the project is the use of an accelerometer for controlling the robot's movement. An accelerometer is a sensor that detects changes in orientation and motion. In this system, it is used as a gesture-based control interface, allowing the user to control the robot by simply tilting or moving a handheld device. This method of control is more intuitive and user-friendly compared to traditional remote controls, as it reduces complexity and improves responsiveness. The robot is built around a microcontroller, which acts as the brain of the system. It processes input signals from the accelerometer and converts them into appropriate commands to drive the motors. The robot can move in multiple directions, navigate through obstacles, and perform inspection tasks effectively. Additional components such as cameras, infrared sensors, or ultrasonic sensors can be integrated to enhance the robot's capability for real-time monitoring and obstacle detection. Overall, this project aims to provide a smart, efficient, and eco-friendly solution for inspection purposes. By combining solar power with accelerometer-based control, the system not only reduces human effort and risk but also promotes the use of sustainable energy in modern robotic applications. This makes it a valuable contribution to the field of automation and intelligent systems.

OBJECTIVE

- To design and develop a robot powered by solar energy
- To utilize renewable energy for efficient and eco-friendly operation
- To implement an accelerometer for tilt, motion, and stability detection
- To enable inspection in hazardous and inaccessible areas
- To reduce human involvement and improve safety
- To achieve real-time monitoring and control of the robot
- To ensure smooth navigation on uneven surfaces
- To minimize operational and maintenance costs.

2. LITERATURE REVIEW

- **Halder, S. & Afsari, K. (2023)** This study presents a comprehensive review of robotic systems used for inspection of buildings and infrastructure. It highlights different robot types such as UAVs and UGVs and emphasizes the importance of sensors and automation in improving inspection efficiency and safety.
- **Macaulay, M.O. & Shafiee, M. (2022)** The authors reviewed machine learning techniques in robotic inspection systems. Their work focuses on how intelligent algorithms help robots analyze data and improve decision-making in inspection tasks, enhancing automation and accuracy.
- **Oliveira, A.K.V., Aghaei, M., & R  ther, R. (2022)** This paper reviews automated inspection of solar power plants using aerial thermography. It demonstrates how robotic systems can efficiently detect faults in solar panels, showing the importance of integrating renewable energy systems with inspection technologies.

- **Ahmed, H., La, H.M., & Gucunski, N. (2020)** The study focuses on robotic platforms for non-destructive evaluation of bridges. It discusses advanced sensors and robotic technologies that improve inspection accuracy and reduce reliance on manual inspection methods.
- **Alhassan, A.B., Zhang, X., & Xu, H. (2020)** This review examines inspection robots used in power transmission lines. It highlights challenges such as navigation, sensing, and environmental conditions, and suggests improvements for future robotic inspection systems.
- **Zhao, J. (2020)** This literature review discusses robotic non-destructive testing (NDT) for infrastructure inspection. It explains how robots can detect hidden defects like corrosion or cracks while preserving structural integrity, making them suitable for industrial inspection tasks.
- **Neto, P., Pires, N., & Moreira, P. (2013)** The authors proposed an accelerometer-based control system for robotic arms. Their research shows that gesture-based control improves user interaction and allows intuitive robot operation, which is directly relevant to accelerometer-controlled inspection robots.
- **Figgis, B., Azid, S.I., & Parlevliet, D. (2025)** This review focuses on unmanned ground vehicles for solar plant inspection. It highlights the growing importance of robotic systems powered by renewable energy and their ability to monitor large-scale solar installations efficiently.

3. HARDWARE COMPONENT

• ACCELEROMETER

An accelerometer is a mechanical or electromechanical device used to measure acceleration, deceleration, tilt, vibration, and shock. The ADXL202E is a compact, low-cost, and low-power 2-axis accelerometer capable of measuring acceleration in the range of $-2g$ to $+2g$ along the X and Y axes.




Fig.1 Accelerometer

It is based on MEMS technology and integrates sensing and signal conditioning on a single chip. The sensor provides PWM (duty-cycle modulated) digital output, which can be directly interfaced with a microcontroller without the need for an analog-to-digital converter. The duty cycle is proportional to acceleration and can be adjusted using an external resistor, while bandwidth is controlled through external capacitors. The pre-assembled module is easy to mount, requires minimal power, and offers fast response, making it suitable for applications such as robotics, guidance systems, automotive systems, and model aircraft.

• Microwave Motion Sensor

HB series of microwave motion sensor module are X-band Mono-static DRO Doppler transceiver front end module. This module is designed for movement detection, like intruder alarms, occupancy modules and other innovative ideas. The module consists of Dielectric Resonator Oscillator (DRO) microwave mixer and patch antenna as in Figure. A Microwave Motion Sensor is an electronic device used to detect movement using microwave radar technology. It emits microwave signals (usually around 10.525 GHz) and measures the reflection of these waves from moving objects using the Doppler Effect. When an object moves within its detection range, the frequency of the reflected waves changes, which the sensor interprets as motion



Fig.2 Microwave Motion Sensor

- **Firebird V (ATMEGA2560)**

Firebird V includes micro controller, sensors, indicators, ZigBee and LCD. Firebird V supports ATMEGA2560 (AVR) micro controller. ATMEGA2560 is a high performance, low power microchip 8-bit AVR RISC based micro controller consists of 256kb ISP flash memory, 8kb SRAM, 4kb EPROM. All AVR microcontrollers can be programmed using In System Programming (ISP), external programmer or using boot loader. Advantage with the boot loader is that one doesn't need any external hardware to load .hex file on the microcontroller. It also protects robots hardware from possible damage due to static electricity and prevents any accidental changes in the fuse settings of the microcontroller. Fire Bird V Omni Directional Robot is based on Fire Bird V ATMEGA2560 platform. It has three omni directional wheels 120 degrees apart. By changing velocity and direction of the wheels robot can move in any direction without changing its orientation.



Fig. 3 Firebird V (ATMEGA2560)

- **DC MOTOR**

A DC motor converts electrical energy into mechanical energy through the interaction of magnetic fields and current-carrying conductors, producing torque and speed as output. Its input is electrical current or voltage. The motor consists of two main parts: the armature, which is the rotating component made of wire coils wound around a core and connected to a rotating shaft, and the stator, which is the stationary part containing the field coils. Electrical contact between the stationary and rotating parts is achieved through commutators and brushes, allowing current to flow to the armature and enabling rotation.



Fig.4 DC Motor

- **ARDUINO**

Arduino is an open-source physical computing platform designed to sense and controls the physical world using a simple microcontroller board and an easy-to-use development environment. It allows users to create interactive projects by reading inputs from sensors or switches and controlling outputs such as motors, lights, and other devices. Arduino boards can operate independently or communicate with a computer, and both the hardware designs and software tools are freely available. The Arduino Uno, based on the ATmega328

microcontroller, is widely used in educational and professional applications. It operates at 5 V with a 16 MHz clock speed and features 14 digital input/output pins (including PWM outputs), 6 analog input pins, 32 KB of flash memory, 2 KB of SRAM, and 1 KB of EEPROM. The board includes a USB interface, external power supply support, and easy-to-use headers for hardware connections. Programs written in a simplified C/C++ language can be uploaded via USB and run autonomously without a computer. Unlike earlier boards, the Arduino Uno uses an ATmega16U2 as a USB-to-serial converter, making it a complete and reliable platform for embedded system development.



Fig.5 ARDUINO

- **MEMS SENSOR**

MEMS (Micro-Electro-Mechanical Systems) are miniaturized devices typically ranging from 1 to 100 micrometers in size, integrating mechanical components, sensors, actuators, and microelectronics on a single chip. These systems are known for their small size, low cost, and high accuracy, making them suitable for a wide range of industrial applications. MEMS sensors detect external physical stimuli such as pressure or acceleration and respond through mechanical action, which is then converted into an electrical signal. MEMS accelerometers are commonly used inertial sensors and are primarily classified into piezoresistive and capacitive types.



Fig.6 MEMS Sensor

While both use internal proof masses that react to acceleration, they differ in how the movement of the proof mass is converted into an electrical signal. Due to their compact design and reliability, MEMS sensors are widely used in applications such as robotics, automotive systems, and motion detection devices.

- **ULTRASONIC SENSOR**

An ultrasonic sensor transmits ultrasonic waves into the air and detects reflected waves from an object. There are many applications for ultrasonic sensors, such as in intrusion alarm systems, automatic door openers and backup sensors for automobiles. Accompanied by the rapid development of information processing technology, new fields of application, such as factory automation equipment and car electronics, are increasing and should continue to do so.



Fig.7 ULTRASONIC SENSOR

- **ZIGBEE MODULE**

Zigbee is a widely used wireless communication technology designed for low data rate, low power applications, particularly in control and sensor networks. Based on the IEEE 802.15.4 standard, Zigbee operates in the 868 MHz, 915 MHz, and 2.4 GHz frequency bands with a maximum data rate of 250 kbps, making it suitable for reliable two-way communication between sensors and controllers in wireless personal area networks (WPANs). A Zigbee network consists of three main devices: a Coordinator, Router, and End Device, with at least one coordinator required to manage and maintain the network. Zigbee supports mesh networking, allowing flexible device placement and improved reliability. Its low power consumption, secure communication, and open protocol architecture make it ideal for industrial automation, instrumentation, and Internet of Things (IoT) applications, where it helps eliminate complex wiring and enables easy system expansion and relocation.



Fig.7 ZIGBEE Module

- **LCD (Liquid Crystal Display)**

LCD (Liquid Crystal Display) is an electronic display device widely used in applications such as mobile phones, calculators, computers, televisions, and embedded systems. LCDs are preferred over multi-segment LEDs and seven-segment displays due to their low cost, ease of programming, ability to display custom characters, and support for simple animations. Compared to CRT displays, LCDs are thinner, lighter, and consume significantly less power. A 16×2 LCD operates by blocking light rather than emitting it, making it energy efficient and suitable for compact electronic devices.



Fig.8 LCD

- **DHT 11 SENSOR**

The DHT11 is a commonly used Temperature and humidity sensor that comes with a dedicated NTC to measure temperature and an 8-bit microcontroller to output the values of temperature and humidity as serial data. The DHT11 sensor can either be purchased as a sensor or as a module. Either way, the performance of the sensor is same. The sensor will come as a 4-pin package out of which only three pins will be used whereas the module will come with three pins as shown above. The only difference between the sensor and module is that the module will have a filtering capacitor and pull-up resistor inbuilt, and for the sensor, you have to use them externally if required.



Fig.9 DHT 11 SENSORLCD

- **LDR (Light Dependent Resistor)**

LDR (Light Dependent Resistor) as the name states is a special type of resistor that works on the photoconductivity principle means that resistance changes according to the intensity of light. Its resistance decreases with an increase in the intensity of light. It is often used as a light sensor, light meter, Automatic street light, and in areas where we need to have light sensitivity. LDR is also known as a Light Sensor. LDR are usually available in 5mm, 8mm, 12mm, and 25mm dimensions. It works on the principle of photoconductivity whenever the light falls on its photoconductive material.

**Fig.10** LDR (Light Dependent Resistor)

- **RELAY**

A relay is an electrically operated switch. Many relays use an electromagnet to operate a switching mechanism mechanically, but other operating principles are also used. Relays are used where it is necessary to control a circuit by a low-power signal (with complete electrical isolation between control and controlled circuits), or where several circuits must be controlled by one signal. A relay is an electrically operated switch. Current flowing through the coil of the relay creates a magnetic field which attracts a lever and changes the switch contacts. The coil current can be on or off so relays have two switch positions and most have double throw (changeover) switch contacts as shown in the diagram

**Fig.11** Relay

4. CONSTRUCTION OF PROJECT

A project on a solar-based robot controlled using an accelerometer is an innovative combination of renewable energy and wireless robotics. The main idea is to build a robot that runs on solar power and can be controlled by hand movements using an accelerometer sensor. This system is energy-efficient and useful in applications like surveillance, remote monitoring, and hazardous environment operations. The construction of this project begins with the solar power system. A solar panel is used to capture sunlight and convert it into electrical energy. This energy is stored in a rechargeable battery, which powers all the components of the robot. A voltage regulator is used to provide a stable voltage supply to sensitive electronic components such as the microcontroller and sensors. The core of the robot is the Firebird V robot platform based on ATmega2560 microcontroller. This acts as the brain of the system, controlling all operations like motor movement, sensor data processing, and communication. The robot is connected to a motor driver module, which helps in controlling the direction and speed of the motors.

The motors are responsible for the movement of the robot (forward, backward, left, and right). For motion detection and obstacle sensing, a microwave motion sensor is used. This sensor detects movement using microwave signals and helps the robot respond to obstacles or motion in its surroundings. It increases the

intelligence and safety of the robot. The main control mechanism is based on an accelerometer sensor. The accelerometer is mounted on a handheld controller (or glove). When the user tilts their hand, the accelerometer senses the change in orientation and sends signals accordingly. These signals are processed using an Arduino or NodeMCU ESP8266, which converts the motion into directional commands.




Fig.12 Circuit Diagram of Project

For wireless communication, a ZigBee module is used. One ZigBee module is connected to the accelerometer controller, and another is connected to the robot. The controller sends commands wirelessly to the robot using ZigBee communication. This allows real-time control without physical connections. The NodeMCU ESP8266 can also be used for IoT functionality. It enables remote monitoring or control over Wi-Fi, allowing the robot to be controlled through a mobile app or web interface. This adds flexibility and modern connectivity to the project. In working, when the user tilts the accelerometer, signals are sent through ZigBee to the Firebird V robot. The microcontroller processes these signals and drives the motors through the motor driver. At the same time, the microwave motion sensor ensures obstacle detection, making the system more responsive and intelligent. The solar panel continuously charges the battery, making the robot energy-efficient and eco-friendly. In conclusion, this project demonstrates the integration of solar energy, wireless communication, and sensor-based control. It is a practical and modern robotic system that highlights the use of renewable energy and smart technologies in automation.

5. WORKING OF PROJECT

The working of the solar-based robot controlled using an accelerometer is based on the integration of renewable energy, wireless communication, and motion sensing technology. The system begins with the solar panel, which captures sunlight and converts it into electrical energy. This energy is stored in a rechargeable battery through a solar charge controller, ensuring proper charging and protection. The stored power is then regulated to a stable voltage and supplied to the entire robot system. The control of the robot is achieved using an accelerometer module placed in a handheld device. When the user tilts the device in different directions (forward, backward, left,

or right), the accelerometer senses the change in orientation and generates corresponding analog or digital signals. These signals are processed by a controller such as Arduino or NodeMCU ESP8266, which converts them into movement commands.



Fig. 13 Final Implementation of Project

These commands are transmitted wirelessly using a ZigBee module. One ZigBee module acts as a transmitter connected to the accelerometer controller, while another module on the robot acts as a receiver. The received signals are sent to the Firebird V robot platform based on the ATmega2560 microcontroller, which processes the commands and decides the direction of movement. The microcontroller then sends control signals to the motor driver module. The motor driver amplifies these signals and drives the motors accordingly, allowing the robot to move in the desired direction. The robot can perform actions like moving forward, backward, turning left, or right based on hand gestures. Additionally, the microwave motion sensor continuously monitors the surroundings. If any motion or obstacle is detected, it sends a signal to the controller, which can stop or adjust the robot's movement to avoid collisions. Overall, the system works efficiently by combining solar energy for power, accelerometer for control, ZigBee for communication, and sensors for safety, making it a smart and eco-friendly robotic solution.

Advantages:

- The robot operates using solar energy, reducing dependence on conventional power sources and promoting eco-friendly, sustainable technology.
- Solar charging minimizes electricity usage and maintenance costs associated with frequent battery replacement or recharging.
- The accelerometer allows intuitive gesture-based control, eliminating the need for joysticks or manual switches.
- The integration of solar panels ensures continuous power supply and efficient energy utilization, increasing the robot's operating time.
- Wireless operation and solar power make the robot portable and suitable for remote or outdoor applications where electricity is unavailable.

6. CONCLUSION

The solar powered inspection robot using an accelerometer presents an innovative and efficient solution to modern inspection challenges in industrial and hazardous environments. By integrating renewable solar energy with advanced sensing technology, the system successfully overcomes the major limitations of traditional inspection methods and conventional robots. The use of solar power ensures sustainable and long-duration operation, reducing dependency on external power sources and minimizing environmental impact. The incorporation of an accelerometer significantly

enhances the robot's performance by enabling accurate motion detection, tilt sensing, and stability control. This allows the robot to navigate uneven terrains smoothly and operate reliably in complex conditions. Additionally, the use of a microcontroller-based control system and wireless communication improves automation, real-time monitoring, and remote accessibility, thereby reducing human effort and risk. Overall, the proposed system offers a cost-effective, eco-friendly, and safe alternative for inspection tasks across various applications such as railways, pipelines, and disaster management. It contributes to the advancement of smart and sustainable technologies in the field of robotics.

With further improvements and integration of additional sensors, this system has the potential to become more autonomous, intelligent, and widely applicable in future industrial and environmental monitoring systems. situation of operating spreadable diseased patients by Doctors. If this technique is improvised more non renewable energy can be saved for our future generation.

7. REFERENCES

- [1]. Ivan S, Sabahudin H, Jovana J. Environmental, Social and Other Non-profit Impacts of Mountain Streams Usage as Renewable Energy Resources. Archives for Technical Sciences/Arhiv za Tehnicke Nauke. 2023 Jul 1(29)
- [2]. <https://doi.org/10.59456/afts.2023.1529.057S>
- [3]. Mohandes M, Schulze F, Rehman S, Suliman W. Cleaning photovoltaic solar panels by drone aerodynamic. In 2021 4th International Symposium on Advanced Electrical and Communication Technologies (ISAECT) 2021 Dec 6 (pp. 1-5). IEEE. <https://doi.org/10.1109/ISAECT53699.2021.9668543>
- [4]. Ledmaoui Y, El Maghraoui A, El Aroussi M, Saadane R, Chebak A, Chehri A. Forecasting solar energy production: A comparative study of machine learning algorithms. Energy Reports. 2023 Nov 1;10:1004-12.
- [5]. <https://doi.org/10.1016/j.egy.2023.07.042>
- [6]. Kadhim MJ, Alradha RM, Jawad HK, Al-Dabbagh B, Al-Khafaji Z. Investigating the Effect of the Yellow Chlorophyll on the Characteristics of Liquid Polyethylene Glycol for Liquid Electrolyte Solar Cells. Natural and Engineering Sciences. 2024 Sep 1;9(2):244-56. <https://doi.org/10.28978/nesciences.1479785>
- [7]. Al-Amri F, Saeed F, Mujeebu MA. Novel dual-function racking structure for passive cooling of solar PV panels—thermal performance analysis. Renewable Energy. 2022 Oct 1;198:100-13.
- [8]. <https://doi.org/10.1016/j.renene.2022.08.047>
- [9]. Gupta M, Dubey AK, Kumar V, Mehta DS. Experimental study of combined transparent solar panel and large Fresnel lens concentrator based hybrid PV/thermal sunlight harvesting system. Energy for Sustainable Development. 2021 Aug 1;63:33-40. <https://doi.org/10.1016/j.esd.2021.05.008>
- [10]. Lee S, An KE, Jeon BD, Cho KY, Lee SJ, Seo D. Detecting faulty solar panels based on thermal image processing. In 2018 IEEE International Conference on Consumer Electronics (ICCE) 2018 Jan 12 (pp. 1-2). IEEE.
- [11]. <https://doi.org/10.1109/ICCE.2018.8326228>
- [12]. Olorunfemi BO, Nwulu NI, Ogbolumani OA. Solar panel surface dirt detection and removal based on arduino color recognition. MethodsX. 2023 Jan 1;10:101967. <https://doi.org/10.1016/j.mex.2022.101967>
- [13]. Zhang X, Rodriguez S. Advanced Optimization Techniques for Vehicle Dynamics in Robotics. Association Journal of Interdisciplinary Technics in Engineering Mechanics. 2023 Oct 9;1(1):1-3.